



LED-1002HD2

Two 9.7" rack-mount monitors feature the latest screen imaging technology for enhance clarity and sharpness. Both analog and digital video will benefit by being viewed on these monitors, and they are the best match for displaying higher resolution megapixel imagery.

Benefits

- LED backlight for better color, longer-life, and lower power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing - 3D Interlace comb filter, DNR, 4H filter
- Built-in stereo speakers
- Durable metal case

Related products

- LED-1002HDL - Flush Mount
- LED-1002HDX - Free standing with no front controls
- LED-1002HDLX - Flush mount
- LED-1002HD - Single 9.7" monitor



Specifications	
Mount	Rackmount (5RU)
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	N/A
Selectable Color Temp.	Yes
Case	Metal
Native Aspect Ratio	4:3
Visible Screen Size (WH)	197.6 x 148.8mm / 7.8" x 5.9"
Resolution	1024(H) x 768(V)
Brightness Rating	400 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.192 (H) x 0.192 (V)mm
Color Depth	262,144
Number of Pixels	786,432
Response Time	2ms/2ms (Rising/Falling)
Audio Power / Speakers	2 x 2 watts
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Pixel Configuration	RGB Vertical Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
DSP-	3D Interlace comb DNR, 4H filter
Dimensions	223 x 222 x 77mm / 8.8" x 8.7" x 3"
Operating Temp/Humidity	32 ~ 104°F or 0 ~ 40°C
Power Requirements	12VDC, 2A, negative ground
Power Consumption	30W (Max)
Composite	BNC IN/OUT jacks x 2
PC	15-pin mini D-sub
HDMI	RCA L/R IN, PC 3.5mm IN
Audio	x1 R/L RCA Input
Power	2.1mm DC IN jack
Weight	Net 1.7 kg / 3.75 lbs/ Gross: TBD