

LED-500X3-3GSDI - Front



LED-500X3-3GSDI

Functional and beautiful, this new generation model includes three LED-backlit, LCD monitors in a rack mount configuration. Each 5" monitor includes a native 3G-SDI input signal that is SMPTE 424M compliant, handling bit-rates of 2.97Gbit/sec which supports 1080p video up to 60 frames per second. This model is an ideal solution for broadcast studio environments that distribute and monitor VOD 1080p streams.

Benefits

- 3G/HD/SD-SDI Input and Output
- Quick access source buttons
- Wide viewing angle
- Up/Down tilting
- Tally function

Related Products

LED-430X4-3GSDI

Specifications	
Model	LED-500X3-3GSDI
Mount	Rack: 3 RU
HD Compatible	yes
Case	Durable metal
Native Aspect Ratio	16:9
Visible Screen Size (WH)	108 x 64.8mm / 4.3" x 2.5" x3
Resolution	800 x 480
Brightness Rating	300 cd/m ² (Nit)
Contrast Ratio	600:1
Back Light	LED (15 K)
Dot Pitch	0.135(H) x 0.135(V)
Colors	16.7M
Response Time	25msec
Viewing Angle (L/R/T/B)	85/85/85/85
Dimensions	19" x 5.25" x 6.9" (3 RU)
Operating Temp/Humidity	32 ~ 185°F or 0 ~ 85°C, 85% RH max.
Power Requirements	12VDC, 4.16A
Power Consumption	30W (max)
Component	[BNC x 3] x 3
Composite	BNC Video IN x 3
S-Video	mini-DIN x 3
PC	D-sub (15 pin) x 3
HDMI	yes
Tally Input	D-sub (9 pin)
Audio	No
Power	screw in DC jack
Weight	Net 5 kg / 10.9 lbs, Gross 6.1 kg / 13.4 lbs

LED-500X3-3GSDI - Back

