

LILLIPUT® 15.6" 23.8" 28" Carry-on 4K Broadcast Director Monitors



MODEL NO.:
BM280-4KS

MODEL NO.:
BM230-4KS

MODEL NO.:
BM150-4KS

Broadcast monitor for 4K/Full HD camcorder & DSLR
Application for taking photos & making movies

3840×2160
Resolution

HDR
3D-LUT


3G-SDI **4K HDMI**

A Better Camera Mate

Matches with world-famous 4K/FHD camera brands, to assist cameraman in better photography experience.

Adjustable Color Space

Native, Rec.709 and 3 User Defined are Optional for Color Space



Accurate Color Calibration

A specific calibration to reproduce the colors of the image color space. Color calibration supports the PRO/LTE version of LightSpace CMS by Light Illusion.



HDR

When HDR is activated, the display reproduces a greater dynamic range of luminosity, allowing lighter and darker details to be displayed more clearly. Effectively enhancing the overall picture quality.



Without HDR

Inaccurate exposure, reduced image detail,
unsatisfactory viewing experience.







With HDR

Enjoy sharper images,
greater detail and richer colors.
Auto / HDR10 are for optional.


3D LUT

Wider color gamut range to make precise color reproduction of Rec. 709 color space with built-in 3D LUT, featuring 3 user logs.



3D LUT LOAD

Supports loading the .cube file via USB flash disk.



Multiple Views Display


It supports quad views splitted from different input signals simultaneously, such as SDI, HDMI, DVI and VGA.

Camera Auxiliary Functions


Plenty of auxiliary functions for taking photos and making movies, such as peaking, false color and audio level meter.



PEAKING FILTER (SDI)



MARKER




AUDIO LEVEL METER / HISTOGRAM



6U Rack Mount BM150-4KS

Intelligent SDI Monitoring

It has a various of mounting methods for broadcast, on-site monitoring and live broadcast van, etc. As well as setup a video wall of rack monitors in control room and see all the scenes. A 6U rack for a customized monitoring solution also can be supported for viewing from different angles and images displays.



Wireless HDMI (optional)

With Wireless HDMI (WHDI) technology, which has a 50-meter transmission distance, supports up to 1080p 60Hz. One transmitter can work with one or more receivers.

SPECIFICATIONS / ACCESSORIES

		BM150-4KS	BM230-4KS	BM260-4KS
DISPLAY	Panel	15.6" 8 bit	23.8" 10 bit	28" 10 bit
	Physical Resolution	3840×2160	3840×2160	3840×2160
	Aspect Ratio	16:9	16:9	16:9
	Brightness	330cd/m²	300cd/m²	300cd/m²
	Contrast	1000:1	1000:1	1000:1
	Viewing Angle (H/V)	176° / 176°	178° / 178°	170° / 160°
INPUT	3G-SDI	1	1	1
	Wireless HDMI	1 (optional)	1 (optional)	1 (optional)
	HDMI	HDMI 2.0×2 (support 4K 60Hz)	HDMI 1.4b×2 (support 4K 30Hz)	
	DVI	1	1	1
	VGA	1	1	1
	Audio	2 (L/R)	2 (L/R)	2 (L/R)
	Tally	1	1	1
	USB	1	1	1
OUTPUT	3G-SDI	1	1	1
AUDIO	Speaker	1	2	2
	Ear Phone Slot	1	1	1
POWER	Current	1.2A (15V)	2.7A (15V)	3.4A (15V)
	Input Voltage	--- DC 12-24V (XLR) ---		
	Battery Plate	--- V-mount/ Anton Bauer mount ---		
	Power Consumption	≤18W	≤41W	≤51W
ENVIRONMENT	Operating Temperature	0℃~60℃	0℃~60℃	0℃~60℃
	Storage Temperature	-20℃~60℃	-20℃~60℃	-20℃~60℃
DIMENSION	Dimension (LWD)(mm)	389×267×38	579×376.5×45	670×425×45
	Dimension (LWD)(with case)	524×305×170	666×417×173	761×474×173
	Weight	3.4kg	8.6kg	9.4kg
	Weight(with case)	12kg	17.1kg	21kg

SDI Format	SMPTE-125M	480i(59.94)
	SMPTE-274M	1080i(60/59.94/50) 1080p(30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-292M	1080p(30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p(60/59.94/50/30/29/25/24/23.98) 720p(60/59.94/50)
	SMPTE-372M	1080i(29.97/25/24/23.98) 1080p(60/59.94/50/30/29/25/24/23.98)
	SMPTE-425M	1080p(60/59.94/50)
	ITU-R BT.656	576i(50)
HDMI Format	4K, 1080p, 1080i, 720p, 576p, 576i, 480p	

ACCESSORIES

1. Folding sun shade cover	1 piece
2. Carry-on suitcase	1 piece
3. 15V 4A DC adapter	1 piece
4. Adapter fixing belt	2 pieces
5. Battery plate bracket	1 piece
6. Base bracket	1 pair
7. V-mount or Anton Bauer mount	1 piece
8. TALLY connector (in bulk)	1 piece
9. Manual	1 copy
10. WHDI Accessories (optional)	1 pair
11. Acrylic screen protector (for BM150 only)(optional)	1 piece

Note: Due to constant effort to improve products and product features, specifications may change without notice.

WWW.LILLIPUT.COM

ZHANGZHOU LILLIPUT ELECTRONIC TECHNOLOGY CO., LTD.

Add : Zong Si Road, Lan Tian Economic Development Zone, Zhang Zhou, Fu Jian, 363005, China
Tel: +86-596-2109661/2109323 Fax: +86-596-2109611 Email: sales@lilliput.com



LILLIPUT® 15.6" 23.8" 28" Carry-on 4K Broadcast Director Monitors



MODEL NO.
BM280-4KS

MODEL NO.
BM230-4KS

MODEL NO.
BM150-4KS

Broadcast monitor for 4K/Full HD camcorder & DSLR
Application for taking photos & making movies

3840×2160
Resolution

HDR
3D-LUT

3G-SDI **4K HDMI**