

MSP 200PRO


PROAV Signal Monitor & Generator



Key Features

- Touch Screen control
- Output a range of signal types
- Set and select from a range of common output formats
- Audio Output test included
- Genlock Y & HS outputs
- Input live signals for preview and inspection
- Test using MPEG from USB Media as source
- On Board Test Pattern Generator
- On board Time Code Generator
- Genlock Y Input
- Remote Control via USB connection
- Preview digital input source on the display
- Output (pass through) digital input source for signal testing

Dimensions




Specification

Connectors	Inputs	Standard:	1 x HDMI 1 x USB 1 x Genlock
		Option Module:	1 x SDI
Connectors	Outputs	Standard:	1 x SDI 1 x DVI 1 x CVBS 2 x Genlock 1 x Audio
	Communication Ports	USB	2.0
Performance	Input Resolution	HDMI:	SMPTE: 625/25/50 PAL 525/29.97/59.94 NTSC 720p50/59.94/60 1080i50/59.95/60 1080p50/59.94/60 1080psf VESA: 800x600@60 1024x768@60 1280x768@60 1280x1024@60 1600x1200@60 1920x1080@60
		SDI:	625/25/50 PAL 525/29.97/59.94 NTSC 720p50/59.94/60 1080i50/59.95/60 1080p50/59.94/60 1080psf
	Output Resolution	SMPTE:	487i@60 483P@60 576i@50 576P@50 720p@23.98/24/25/29.97/30/50/59.94/60 1080p@23.98/24/25/29.97/30/50/59.94/60
		VESA:	640x480@60/75/85 800x600@60/75/85 1024x768@60/75/85 1028x1024@60/75/85 1028x800@60 1360x768@60 1366x768@60 1400x1050@60 1440x900@60 1600x1200@60 1680x1050@60 1920x1200@60 2048x1152@60 2560x812@60 2560x816@60
Standard Supported	SDI:	SD-SDI, HD-SDI, 3G-SDI	
	CVBS	PAL, NTSC	
	HDMI:	1.3	
	USB	2.0	
	VGA	VESA	
Power	External	Input Voltage	12DC (via Plug Pack)
	Battery (Optional)	Max Power	12W
Type		Lithium Ion	
Cell		18650	
Quantity		2pcs	
Voltage		3.7V	
Capacity		1500Mah	
Recharge Time		1 hr	
Size		65mm (length) x 18mm (dia)	
Environment	Temperature	0 C~45°C	
	Humidity	10%~85%	
Physical	Weight	0.83kg (Net Weight)	
	Dimensions	219mm x 148.5mm x 32mm (Device Dimension)	

Order Codes

Product Code	Item
651-0200-01-0	MSP 200PRO (with case)
490-5353-02-0	SDI Input Module Option for MSP 200PRO
950-0006-01-0	Battery Li-on 18650 3.7V 1500mAH
690-0001-01-0	Stand for MSP 200PRO

Application



Tel: +86-592-5771197 Fax: +86-592-5788216
 E-mail: sales@rgblink.com http://www.rgblink.com
 Headquarter: S601~604, 606, 607, 504 Weiye Building Torch Hi-Tech Industrial
 Development Zone, Xiamen, Fujian Province, P.R.C



Specifications are correct at time of printing and subject to change or alteration without notice.