

ONE SHEE

Overview

The PDL-F Remote Live 2 Compact Follow Focus Control harnesses the power and precision of PD Movie's popular follow focus systems in a compact control set perfect for both camera stabilizing and traditional camera setups. The PDL-F attaches easily to most rigs. Simply install the precision motor onto either a 15 or 19mm rod and firmly lock its drive gear into the gearing of your lens; its 0.8 pitch gear is compatible with most common cinema lenses. Then, attach the lens control module to your mounting point of choice (less than 1" in diameter), and provide power using the D-tap to lemo adapter. After installing, simply push the control set's button to start and calibrate the unit. Once you do that, your follow focus is ready to use. With full tactile operation, the PDL-F reacts according to how you maneuver the control and not to a preset speed or programmed reaction. Its compact size is a welcome inclusion to your camera rig even those requiring lighter payloads.



PDL-F | Compact Follow Focus Control Kit (PD Movie) | UPC Code: 847983018567

Special Features

- Bring Control of your lens's focus right to your fingertips
- Automatically calibrates to the mapping of your lens
- Simple, single button system settings control

ikan

- Single focus unit can control multiple motors simultaneously
- Compact yet powerful motor can handle both subtle and rapid focus pulls with ease
- Precision motor attaches to both 15mm and 19mm rods (with included sleeve installed)
- Focus control attaches to most square/round handles less than 1" in diameter

Recommended For

- Live Production
- Steady Rigs & Gimbals
- Run-and-Gun Shooters



www.facebook.com/ikanseeit

www.twitter.com/ikancorp

www.vimeo.com/ikancorp



www.youtube.com/ikancorp

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

PDL-F

Features you need, Prices you want.

Precision Motor

The precise movement of the PD3-M motor follows every nuanced adjustment you make on the focus control.

Get Attached

The PDL-F installs quickly to almost any camera setup that incorporates mounting rods.

Simple to Operate

A simple "one-button" control makes calibrating and changing the settings a breeze.

Control Multiple Motors

One single control can power numerous motors, perfect for setting up elaborate 3D and special effects rigs.

Lightweight Yet Effective

While powerful enough to be used in traditional camera setups, the PDL-F is perfect for lightweight applications such as a gimbal or Steadicam operation.

What's Included

- 1 x 19mm x 15mm Bushing
- 1 x D-TAP to LEMO Power Cable
- 1 x LEMO to LEMO Cable
- 1 x PD-TC-F Thumb Control
- 1 x PD3-M Motor

| Specifications | |
|-----------------------|---|
| Cable Length | 39" (Teether) 27" (D-TAP) |
| Channels | 6 Assignable Channels |
| Controllable Channels | 1 |
| Connection | 6-Pin LEMO (Power and Teether) |
| Torque Max | 0.5 Nm Max |
| Gear Pitch | 0.8 (40 Teeth) |
| Noise | <28 db |
| Motor | German Imported, High Precision Brushless Motor |
| Input Voltage | 6-Pin 9-18V |
| Mount | 15-19mm Rods |

Shipping Specifications

PD PD

PD

PD

PD

GR

| omphing opcomotions | |
|---------------------|--------------|
| Shipping Dimensions | 8 x 8 x 4 in |
| Shipping Weight | 1.5 lbs |

Optional Accessories

| D-TC-F D-DTAP | Thumb Controller for PDL-F <i>(PD Movie)</i> Remote Air Pro D-Tap to 4-Pin LEMO Cable <i>(PD Movie)</i> |
|------------------|--|
| | |
| D-RNG | 15mm to 19mm Step Down Ring (PD Movie) |
| D-TC-F | Thumb Controller for PDL-F (PD Movie) |
| 03-M | Remote Air Pro Slave Motor (PD Movie) |
| R-T03 | Gravity 3-Axis Handheld Gimbal System for Cinema |
| | Cameras & DSLRs with Motion Mimicking Control System |
| | & Hard Case (Tilta) |
| | |

