



LED-1003HD

This 9.7" LED-backlit monitor features the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on this monitor, and it is the best match for displaying higher resolution megapixel imagery.

Benefits

LED backlight for better color, longer-life, and lower power
Wide viewing angle
Excellent contrast ratio
Very fast response time
Image enhancing - 3D Interlace comb filter, DNR, 4H filter
Durable metal case

Accessories

DC-1500 Factory approved car cord HM-401 Under-cabinet hinge mount WM-31 Wall mount bracket (fixed)

WM-302 Wall mount with swing arm & 4-way adjustable

Related products

LED-1002HD2 - Dual 9.7" monitors in a rack mount

Specifications	
Mount	VESA 75x75mm and 100x100mm, 1/4-20 pa on top, removable desk stand
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Metal
Native Aspect Ratio	4:3
Visible Screen Size (WH)	7.8" x 5.9" / 197.6 x 148.8mm
Resolution	1024(H) x 768(V)
Brightness Rating	400 cd/m² (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.192 (H) x 0.192 (V)mm
Color Depth	262,144
Number of Pixels	786,432
Response Time	2ms/2ms (Rising/Falling)
Audio Power / Speakers	2 x 2 watts
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Digital Signal Processing	3D Interlace comb DNR, 4H filter
Dimensions w/o desk stand	8.8" x 7.8" x 1.9" / 223.5 x 198 x 48.3mm
Operating Temp/Humidity	32 ~ 104°F / 0 ~ 40°C
Power Requirements	12VDC, 2A, negative ground
Power Consumption	30 watts (Max)
Composite	x2 BNC Inputs; x2 BNC Outputs
PC	x1 15-pin mini D-sub
HDMI	x1 Input
Audio	x1 RCA L/R Input; x1 PC 3.5mm Input
Power	x1 2.1mm DC Input
rowei	AT EITHIN DO HIPGE

Specifications subject to change.