

USER MANUAL

Portable Travel Charger

1. Specs:

- (1) Smart design, conveniently portable.
- (2) Safe and reliable, with PCB protection.

2. How to use

- (1) Please connect D-tap of the charger cable onto that of Battery, the indicator turns green.
- (2) Through AC 90-240V, RED indicator means charge work, GREEN Indicator means charge fully.



CAUTION

There is D tap warning "positive" and "negative" in the charger and battery; please assure the connection in correct position with "positive to positive" "negative to negative". Our company will not offer any warranty service if the wrong connection leads to security matter or device damage.



V-LOCK/GOLD LOCK Dual Charger

1. Specs:

- V-LOCK/GOLD LOCK is the dual charger for professional camera battery.
S/A charger is for V-LOCK/GOLD LOCK.
Charge two batteries simultaneously.
Power the camera as power adapter.

2. Operation:

- Charge operation:
- Connect the power cable onto charger and 100-240V AC power.
 - Connect the battery onto the plate of the charger.
 - Switch on charge section, the indicator RED means "charge work start".
 - Indicator ORANGE means nearly charge fully.
 - Indicator GREEN means charge fully.
 - Switch off and take off the battery from the charger.

Adapter operation:

- Connect the adapter cable onto adapter connector of the charger.
- Power cable by 100-240V connection, switch on adapter, indicator RED means powering the camera.

V-LOCK/GOLD LOCK Four-Channel Charger

1. Product description:

- V-LOCK/GOLD LOCK is the dual charger for professional camera battery.
S/A charger is for V-LOCK/GOLD LOCK.
Charge four batteries simultaneously.
Power the camera as power adapter.

2. Operation:

- Charge operation:
- Connect the power cable onto charger and 100-240V AC power.
 - Connect the battery onto the plate of the charger.
 - Switch on charge section, the indicator RED means "charge work start".
 - Indicator ORANGE means nearly charge fully.
 - Indicator GREEN means charge fully.
 - Switch off and take off the battery from the charger.

Adapter operation:

- Connect the adapter cable onto adapter connector of the charger.
- Power cable by 100-240V connection, switch on adapter, indicator RED means powering the camera.

Technical Specs. For Lithium Battery Charger

Model	Input	Charge output	Adapter output	Applicable battery	Size	Weight	Working temperature
RL-4KS	AC 100V-240V 50/60Hz	DC 16.8V, 3A	DC 15V, 4A	V-LOCK BATTERY	256*118*188mm	2.75KG	-10 C ~40 C
RL-4KA	AC 100V-240V 50/60Hz	DC 16.8V, 3A	DC 15V, 4A	AB BATTERY	256*118*188mm	2.67KG	-10 C ~40 C
RL-2KS	AC 100V-240V 50/60Hz	DC 16.8V, 3A	DC 15V, 4A	V-LOCK BATTERY	228*140*86mm	1.72KG	-10 C ~40 C
RL-2KA	AC 100V-240V 50/60Hz	DC 16.8V, 3A	DC 15V, 4A	AB BATTERY	228*140*86mm	1.68KG	-10 C ~40 C
RL-T1A	AC 100V-240V 50/60Hz	DC 16.8V, 3A	DC 15V, 4A	V-LOCK & AB BATTERY	190*120*43mm	0.33KG	0 C ~40 C

CAUTION

Thank you so much for selecting Rolux, please read the user manual before you use our product. TO avoid unnecessary loss, please call us when you have any question, we will offer you on-time assistance.

- 1、 Please check the package after you receive the parcel, product might be damaged if package is broken.
- 2、 Prevent the product from being deformed, otherwise it will lead to the damage of electrical parts.
- 3、 Please don't dismantle the product housing so as to avoid unexpected trouble.

ROLUX[®]

